
restfulgrok Documentation

Release 1.0.5

Espen Angell Kristiansen

May 18, 2012

CONTENTS

Fabric (<http://fabfile.org>) tasks for Amazon Web Services with some extra utilities for Ubuntu.

**CHAPTER
ONE**

INSTALL

```
$ pip install awsfabRICTasks
```


CODE AND ISSUES

Get the sourcecode, and submit issues at our github repo: <https://github.com/espennak/awsfabRICTasks>

GETTING STARTED

3.1 Fabric

Learn how to use [Fabric](#).

3.2 The awsfab command

Fabric is great for remote execution because it allows you to run a task on any SSH-server with the following syntax:

```
$ fab -H server1,server2,server3 task1 task2
```

The problem with Fabric on AWS EC2 is that we do not have a static dns address to give to `-H`. `awsfab` wraps `fab` and allows us to use:

```
$ awsfab -E <Name-tag of an EC2 instance>,<Name-tag of another....> task1 task2
```

If your instance is not tagged with a name (the tag must be capitalized: `Name`), you can use `--ec2ids` instead.

3.3 Required settings

See `awsfab_settings.py` — *Settings*.

MAKING A FABFILE.PY AND USE AWSFABRICTASKS

4.1 Example fabfile.py

Create a `fabfile.py` just as you would with Fabric, and import tasks from `awsfabriktasks`:

```
from fabric.api import task, run
from awsfabriktasks.decorators import ec2instance

#####
# Add some of our own tasks
#####

@task
def uname():
    """
    Run ``uname -a``
    """
    run('uname -a')

@task
@ec2instance(nametag='tst')
def example_nametag_specific_task():
    """
    Example of using ``@ec2instance``.
    Enables us to run::

        awsfab example_nametag_specific_task
    and have it automatically use the EC2 instance tagged with ``Name="tst"``.
    """
    run('uname -a')

#####
# Import awsfab tasks
#####
from awsfabriktasks.ec2.tasks import *
from awsfabriktasks.regions import *
from awsfabriktasks.conf import *
```

4.2 Using the example

List basic information about your instances with:

```
$ awsfab ec2_list_instances
```

Start one of your existing EC2 instances (the example assumes it is tagged with Name="mytest"):

```
$ awsfab -E mytest ec2_start_instance
```

Login (SSH) to the instance we just started:

```
$ awsfab -E mytest ec2_login
```

See:

```
$ awsfab -l
```

or [Tasks](#) for more tasks.

4.3 Launch/create new EC2 instances

See [Example awsfab_settings.py](#) for an example of how to setup your EC2 launch configurations. After you have added EC2_LAUNCH_CONFIGS to your `awsfab_settings.py`, simply run:

```
$ awsfab ec2_launch_instance:<nametag>
```

where `<nametag>` is the name you want to tag your new instance with. You will be asked to choose a config from EC2_LAUNCH_CONFIGS, and to confirm all your choices before the instance is created.

MORE TASK-EXAMPLES

The best examples are the provided tasks. Just browse the source, or use the [source] links in the *tasks docs*.

DOCUMENTATION

6.1 Tasks

6.1.1 awsfabrictasks.ec2.tasks

General tasks for AWS management.

`awsfabrictasks.ec2.tasks.ec2_add_tag`

Add tag to EC2 instance. Fails if tag already exists.

Parameters

- **tagname** – Name of the tag to set (required).
- **value** – Value to set the tag to. Default to empty string.

`awsfabrictasks.ec2.tasks.ec2_set_tag`

Set tag on EC2 instance. Overwrites value if tag exists.

Parameters

- **tagname** – Name of the tag to set (required).
- **value** – Value to set the tag to. Default to empty string.

`awsfabrictasks.ec2.tasks.ec2_remove_tag`

Remove tag from EC2 instance. Fails if tag does not exist.

Parameters **tagname** – Name of the tag to remove (required).

`awsfabrictasks.ec2.tasks.ec2_launch_instance`

Launch new EC2 instance.

Parameters

- **name** – The name to tag the EC2 instance with (required)
- **configname** – Name of the configuration in `awsfab_settings.EC2_LAUNCH_CONFIGS`. Prompts for input if not provided as an argument.
- **noconfirm** – Do not require the user to confirm creating the instance? Defaults to False.

`awsfabrictasks.ec2.tasks.ec2_start_instance`

Start EC2 instance.

Parameters **nowait** – Set to True to let the EC2 instance start in the background instead of waiting for it to start. Defaults to False.

`awsfabrictasks.ec2.tasks.ec2_stop_instance`

Stop EC2 instance.

Parameters `nowait` – Set to True to let the EC2 instance stop in the background instead of waiting for it to start. Defaults to False.

`awsfabrictasks.ec2.tasks.ec2_list_instances`

List EC2 instances in a region (defaults to `awsfab_settings.DEFAULT_REGION`).

Parameters

- `region` – The region to list instances in. Defaults to “`awsfab_settings.DEFAULT_REGION`.
- `full` – Print all attributes, or just the most useful ones? Defaults to False.

`awsfabrictasks.ec2.tasks.ec2_print_instance`

Print EC2 instance info.

Parameters `full` – Print all attributes, or just the most useful ones? Defaults to False.

`awsfabrictasks.ec2.tasks.ec2_login`

Log into the host specified by `-hosts`, `-ec2names` or `-ec2ids`.

Aborts if more than one host is specified.

6.1.2 awsfabrictasks.ec2.regions

6.2 API

6.2.1 awsfabrictasks.conf

`class awsfabrictasks.conf.Settings`

Bases: object

Settings object inspired by django.conf.settings.

`as_dict()`

Get all settings (uppercase attributes on this object) as a dict.

`pprint()`

Prettyprint the settings.

`awsfabrictasks.conf.print_settings`

Pretty-print the settings as they are seen by the system.

6.2.2 awsfabrictasks.utils

`awsfabrictasks.utils.sudo_chattr(remote_path, owner=None, mode=None)`

Run `sudo_chown()` and `sudo_chmod()` on `remote_path`. If owner or mode is None, their corresponding function is not called.

`awsfabrictasks.utils.sudo_chmod(remote_path, mode)`

Run sudo chmod <mode> `remote_path`.

`awsfabrictasks.utils.sudo_chown(remote_path, owner)`

Run sudo chown <owner> `remote_path`.

`awsfabrictasks.utils.sudo_mkdir_p(remote_path, **chattr_kw)`

sudo mkdir -p <remote_path> followed by :func:`sudo_chattr`(`remote_path`, `**chattr_kw`).

```
awsfabriktasks.utils.sudo_upload_dir(local_dir, remote_dir, **chattr_kw)
    Upload all files and directories in local_dir to remote_dir. Directories are created with sudo_mkdir_p() and files are uploaded with sudo_upload_file(). chattr_kw is forwarded in both cases.

awsfabriktasks.utils.sudo_upload_file(local_path, remote_path, **chattr_kw)
    Use sudo to upload a file from local_path to remote_path and run sudo_chattr() with the given chattr_kw as arguments.
```

6.2.3 awsfabriktasks.ubuntu

Ubuntu utilities.

```
awsfabriktasks.ubuntu.set_locale(locale='en_US')
    Set locale to avoid the warnings from perl and others about locale failures.
```

6.2.4 awsfabriktasks.ec2.api

```
exception awsfabriktasks.ec2.api.Ec2RegionConnectionError(region)
```

Bases: exceptions.Exception

Raised when we fail to connect to a region.

```
exception awsfabriktasks.ec2.api.WaitForStateError
```

Bases: exceptions.Exception

Raises when wait_for_state() times out.

```
class awsfabriktasks.ec2.api.Ec2InstanceWrapper(instance)
```

Bases: object

Wraps a boto.ec2.instance.Instance with convenience functions.

Variables `instance` – The boto.ec2.instance.Instance.

Parameters `instance` – A boto.ec2.instance.Instance object.

```
add_instance_to_env()
```

Add self to fabric.api.env.ec2instances[self.get_ssh_uri()], and register the key-pair for the instance in fabric.api.env.key_filename.

```
classmethod get_by_instanceid(instanceid)
```

Connect to AWS and get the EC2 instance with the given instance ID.

Parameters `instanceid_with_optional_region` – Parsed with parse_instanceid() to find the region and name.

Raises

- **Ec2RegionConnectionError** – If connecting to the region fails.
- **LookupError** – If the requested instance was not found in the region.

Returns A Ec2InstanceWrapper containing the requested instance.

```
classmethod get_by_name_tag(instancename_with_optional_region)
```

Connect to AWS and get the EC2 instance with the given Name-tag.

Parameters `instancename_with_optional_region` – Parsed with parse_instancename() to find the region and name.

Raises

- **Ec2RegionConnectionError** – If connecting to the region fails.
- **LookupError** – If the requested instance was not found in the region.

Returns A `Ec2InstanceWrapper` containing the requested instance.

classmethod `get_by_tagvalue(tags={}, region=None)`

Connect to AWS and get the EC2 instance with the given tag:value pairs.

:param tags A string like ‘role=testing,fake=yes’ to AND a set of ec2 instance tags

Parameters `region` – optional.

Raises

- **Ec2RegionConnectionError** – If connecting to the region fails.
- **LookupError** – If no matching instance was found in the region.

Returns A list of `:class:`Ec2InstanceWrapper``s containing the matching instances.

classmethod `get_from_host_string()`

If an instance has been registered in `fabric.api.env` using `add_instance_to_env()`, this method can be used to get the instance identified by `fabric.api.env.host_string`.

get_ssh_key_filename()

Get the SSH indentify filename (.pem-file) for the instance. Searches `awsfab_settings.KEYPAIR_PATH` for "`<instance.key_name>.pem`".

Raises `LookupError` If the key is not found.

get_ssh_uri()

Get the SSH URI for the instance.

Returns “`<instance.tags['awsfab-ssh-user']>@<instance.public_dns_name>`”

prettyname()

Return a pretty-formatted name for this instance, using the Name-tag if the instance is tagged with it.

```
awsfabictasks.ec2.api.create_hostsfile_from_nametags(nametags=[], suffix='ec2private', hostsfile_template='\n127.0.0.1\nlocalhost\n#\n\tThe following lines are desirable for IPv6 capable hosts\n::1\tip6-localhost\nip6-loopback\nfe00::0\tip6-localnet\nff00::0\tip6-mcastprefix\nff02::1\tip6-allnodes\nff02::2\tip6-allrouters\nff02::3\tip6-allhosts\n\n{custom_hosts}\n')
```

Create a `/etc/hosts` file from the list of nametags. The result will be a hostsfile with `private_ip_address` as IP, and `nametag+suffix` as hostname.

```
awsfabictasks.ec2.api.ec2_rsync(local_dir, remote_dir, rsync_args=' -av', sync_content=False)
rsync local_dir into remote_dir on the current EC2 instance (the one returned by Ec2InstanceWrapper.get_from_host_string()).
```

Parameters sync_content – Normally the function automatically makes sure local_dir is not suffixed with /, which makes rsync copy local_dir into remote_dir. With sync_content=True, the content of local_dir is synced into remote_dir instead.

awsfabrictasks.ec2.api.**parse_instanceid**(instanceid_with_optional_region)

Parse instance id with an optional region-name prefixed. Region name is specified by prefixing the instanceid with <regionname>::.

Returns (region, instanceid) where region defaults to awsfab_settings.DEFAULT_REGION if not prefixed to the id.

awsfabrictasks.ec2.api.**parse_instancename**(instancename_with_optional_region)

Just like [parse_instanceid\(\)](#), however this is for instance names. We keep them as separate functions in case they diverge in the future.

Returns (region, instanceid) where region defaults to awsfab_settings.DEFAULT_REGION if not prefixed to the name.

awsfabrictasks.ec2.api.**print_ec2_instance**(instance, full=False, indentspaces=3)

Print attributes of an ec2 instance.

Parameters

- **instance** – A boto.ec2.instance.Instance object.
- **full** – Print all attributes? If not, a subset of the attributes are printed.
- **indentspaces** – Number of spaces to indent each line in the output.

awsfabrictasks.ec2.api.**wait_for_running_state**(instanceid, **kwargs)

Shortcut for wait_for_state(instanceid, 'running', **kwargs).

awsfabrictasks.ec2.api.**wait_for_state**(instanceid, state_name, sleep_intervals=[15, 5], last_sleep_repeat=40)

Poll the instance with instanceid until its state_name matches the desired state_name.

The first poll is performed without any delay, and the rest of the polls are performed according to sleep_intervals.

Parameters

- **instanceid** – ID of an instance.
- **state_name** – The state_name to wait for.
- **sleep_intervals** – List of seconds to wait between each poll for state. The first poll is made immediately, then we wait for sleep_intervals[0] seconds before the next poll, and repeat for each item in sleep_intervals. Then we repeat for last_sleep_repeat using the last item in sleep_intervals as the timeout for each wait.
- **last_sleep_repeat** – Number of times to repeat the last item in sleep_intervals. If this is 20, we will wait for a maximum of sum(sleep_intervals) + sleep_intervals[-1]*20.

awsfabrictasks.ec2.api.**wait_for_stopped_state**(instanceid, **kwargs)

Shortcut for wait_for_state(instanceid, 'stopped', **kwargs).

6.2.5 awsfabrictasks.decorators

awsfabrictasks.decorators.**ec2instance**(nametag=None, instanceid=None)

Wraps the decorated function to execute as if it had been invoked with --ec2names or --ec2ids.

6.3 awsfab_settings.py — Settings

6.3.1 Required setup

awsfabictasks uses a settings system similar to the Django settings module. You add your settings to `awsfab_settings.py`.

Required configuration

Create a file named `awsfab_settings.py`, and add your AWS Security credentials:

```
AUTH = {'aws_access_key_id': 'Access Key ID',
        'aws_secret_access_key': 'Secret Access Key'}
```

You find these under My account → Security Credentials on <http://aws.amazon.com/>.

.pem-key

The `.pem`-keys (key pairs) for your instances (the ones used for SSH login) must be added to `~/.ssh/` or the current directory. You can change these directories with the `awsfab_settings.KEYPAIR_PATH` variable (see *Default settings*).

6.3.2 Local override

You may override settings in `awsfab_settings_local.py`, which is typically used to store authentication credentials outside your version control system (i.e: with git you would add `awsfab_settings_local.py` to `.gitignore`).

6.3.3 Example awsfab_settings.py

```
# Config file for awsfabictasks.
#
# This is a Python module, and it is imported just as a regular Python module.
# Every variable with an uppercase-only name is a setting.

AUTH = {'aws_access_key_id': 'XXXXXXXXXXXXXXXXXXXX',
        'aws_secret_access_key': 'xxxxxxxxxxxxxxxxxxxxxxxxxxxx'}

DEFAULT_REGION = 'eu-west-1'

#####
# Self documenting map of AMIs
# - You are not required to use this, but it makes it easier to read
#   EC2_LAUNCH_CONFIGS.
#####
ami = {
    'ubuntu-10.04-lts': 'ami-fb665f8f'
}

#####
# Configuration for ec2_launch_instance
```

```
#####
EC2_LAUNCH_CONFIGS = {
    'ubuntu-10.04-lts-micro': {
        # Ami ID (E.g.: ami-fb665f8f)
        'ami': ami['ubuntu-10.04-lts'],
        # One of: m1.small, m1.large, m1.xlarge, c1.medium, c1.xlarge, m2.xlarge, m2.2xlarge, m2.4xla
        'instance_type': 't1.micro',
        # List of security groups
        'security_groups': ['allowssh'],
        # Use the ''list_regions'' task to see all available regions
        'region': DEFAULT_REGION,
        # The name of the key pair to use for instances (See http://console.aws.amazon.com -> EC2 ->
        'key_name': 'awstestkey',
        # The availability zone in which to launch the instances. This is
        # automatically prefixed by ''region''.
        'availability_zone': 'b',
        # Tags to add to the instances. You can use the ''ec2_*_tag'' tasks or
        # the management interface to manage tags. Special tags:
        #   - Name: Should not be in this dict. It is specified when launching
        #           an instance (needs to be unique for each instance).
        #   - awsfab-ssh-user: The ''awsfab'' tasks use this user to log into your instance.
        'tags': {
            'awsfab-ssh-user': 'ubuntu'
        }
    }
}

#####
# Add your own settings here
#####

MYCOOLSTUFF_REMOTE_DIR = '/var/www/stuff'
```

6.3.4 Default settings

`awsfabictasks.default_settings.AUTH = {}`

The AWS access key. Should look something like this:

```
AUTH = {'aws_access_key_id': 'XXXXXXXXXXXXXXXXXXXX',
        'aws_secret_access_key': 'aaaaaaaaaaaa\BBBBBBBB\dsaddad'}
```

`awsfabictasks.default_settings.DEFAULT_REGION = 'eu-west-1'`

The default AWS region to use with the commands where REGION is supported.

`awsfabictasks.default_settings.EC2_INSTANCE_DEFAULT_SSHUSER = 'root'`

Default ssh user if the awsfab-ssh-user tag is not set

`awsfabictasks.default_settings.EC2_LAUNCH_CONFIGS = {}`

Configuration for ec2_launch_instance (see the docs)

`awsfabriktasks.default_settings.EXTRA_SSH_ARGS = '-o StrictHostKeyChecking=no'`

Extra SSH arguments. Used with ssh and rsync.

`awsfabriktasks.default_settings.KEYPAIR_PATH = ['.', '~/.ssh/']`

Directories to search for “<key_name>.pem”. These paths are filtered through os.path.expanduser, so paths like `~/.ssh/` works.

INDICES AND TABLES

- *genindex*
- *modindex*
- *search*

PYTHON MODULE INDEX

a

```
awsfabRICTasks.conf, ??  
awsfabRICTasks.decorators, ??  
awsfabRICTasks.default_settings, ??  
awsfabRICTasks.ec2.api, ??  
awsfabRICTasks.ec2.tasks, ??  
awsfabRICTasks.regions, ??  
awsfabRICTasks.ubuntu, ??  
awsfabRICTasks.utils, ??
```